

1.5-30MHz 16Way 1U High Isolation Multicoupler "MC-HF0116A-HI"

The MC-HF0116A-HI, is a HF 16 way multicoupler. It is a high isolation solution for coupling up to 16 HF receivers to a single antenna. Using a unique feedback circuit, exceptional linearity performance is achieved. Internally the topology of the amplifier chain allows for exceptional isolation. The unit is provided in a 19" 1U high rack mounted case. Health monitoring is provided. Local LED indicates 'STATUS', an opto-coupler output allows remote indication of 'STATUS'. Lighting protection is incorporated. Optional Filter may be fitted to reject LF/MF and VHF 88-108 Broadcast services.



Specification:

Parameter	Limits
Freq:	1.5-30Mhz
Gain:	0 – 2dB nominal
Gain Variation:	+/- 1dB max
Noise Figure:	10dB max. (typ 9.3dB)
Number of inputs:	1
Number of outputs:	16
Input Output Impedance	50 Ohms
Output Intercept (OPIP):-	3rd Order >+30dBm min . (typ +35dBm) 2nd order >+70dBm min. (typ +78dBm) P1dB > 16dB
VSWR INput 50 Ohm	1.5:1 max. (Return Loss >14dB)
VSWR output 50 Ohm	1.3:1 max. (Return Loss >17.7dB)
Isolation - Output to output: Output to input:	>50dB min >60dB min
Max. input signal CW	20dBm cont.
Power:	Mains 110/220V ac. Power 30W

Alarms/Protection CCT

Alarms – The multicoupler has a 'on board' health monitoring circuit which monitors the operation of the active amplifier. Should a fault occur the 'Status' LED on the front panel will change from 'Green' to 'Red'. In addition there are 16 independent LEDs on the rear panel which are green when ok, and off when fail. There are two failure modes:

Critical – Is when a single point failure affects all outputs. In this case the front panel alarm LED will be Red and all rear Green LED's will be extinguished.

Non-Critical – when a single output only is affected the front panel alarm LED will be RED and only the output(s) affected have an extinguished LED on the rear panel. In a non-critical alarm condition the 'good' outputs (Green) can still be used.

Electrical:

AC Mains Power Connector -	3 Pin IEC male connector.
AC Mains Switch -	Illuminating Mains Switch is front panel located
AC Mains Fuse -	Rear panel mounted
DC Fuse -	Front panel mounted
110/220AC Selector -	Rear Panel switch

Mechanical

Connectors: I/P	1 x N – Type Female
O/P	16 x RF BNC sockets
	Power/Alarm DC connector is Molex , Mini fit Jr.

Dimensions: 19", 1U rack mount,

Environmental

Temp range:	operating: -0C to +50C storage: -20C to +70C
Humidity	Operating 10% to 90% (Non condensing) Storage 5% to 95% (Non condensing)
EMI	FCC Part 15

Cooling Case is vented top and bottom requiring airflow

Options: - 1 –The unit can be preceded by a HF band pass filter unit such as the FL003. This can help with strong out of band. Broadcast signals.

